



技术规格参数 Technical Specifications and Parameters

| | | | |
|-------------------------------|---|---|--|
| 通路数 (Circuits) | 2~96 (可定制更多) (more options available) | 电流 (Current) | 信号 (2A) ;功率10A/路 Signal:2A ; Power:10A/Ring |
| 电压 (Voltage) | 600VDC/VAC | 最高转速 (Max Speed) | 建议1-2500RPM之间 Suggest between 1-2500 |
| 外壳材质 (Housing Material) | 铝轴塑盖 (Aluminum shaft plastic cover) | 扭矩 (Torque) | 0.02N.m+0.01N.m/6路(ring) |
| 工作寿命 (Working Life) | >4千万转 (按等级请咨询) >4 million (Please consult by grade) | 接触材料 (Contact Material) | 信号: 金合金; 功率: 银合金 Signal: gold alloy; Power: Silver alloy |
| 电气噪音 (Electrical noise) | < 0.01 (Ω) | 接触电阻 (Contact Resistance) | < 1毫欧 (mΩ) |
| 耐压强度 (Dielectric strength) | 1000VDC@50Hz | 导线规格 (Electrical Wire) | UL Teflon@Awg22,Awg16 |
| 绝缘强度 (Insulation Strength) | 1000M@600VDC | 导线线长 (Wire Length) | 300mm |
| 工作温度 (Working Temp) | -40°C to 80°C |  | |
| 工作湿度 (Humidity) | 10% to 85% RH | | |
| 防护等级 (Protection Grade) | IP51 | | |
| 认证 (Certificate) | ROHS | | |